

## 55" Full-HD LED



### Product Features

- Industrial level DID LED panel, suitable for extensive 7\*24 continuous works
- High fidelity digital processing, brilliant and vivid video.
- 5.8ms fast response time. no picture ghosting
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- Brightness smart detection, power-saving
- Using Tamper-proof metal housing, no radiation
- Professional thermal design to extend equipment lifespan

### Technical Specifications

<b>Model</b>	DE-LED55I	
<b>System</b>		
<b>Diagonal</b>	54.6"(16:9)	
<b>Resolution</b>	1920×1080 (FHD)	
<b>Backlight</b>	LED	
<b>Brightness/Luminance (Standard)</b>	700 cd/m <sup>2</sup>	
<b>Contrast</b>	4500:1	
<b>Angle of view</b>	178° /178° (vertical/horizontal)	
<b>Response time</b>	5.8ms	
<b>Signals</b>		
<b>Input</b>	<b>standard</b>	VGA(D-Sub)×1, CVBS(BNC)×2, DVI-D×1, HDMI×1, RS232×1
	<b>optional</b>	Audio in×1, RJ45×1, HDCVI×1, SDI×1, DP×1
<b>Output</b>	<b>Standard</b>	CVBS(BNC)×2, RS232×1
	<b>optional</b>	DP×1

General	
Consumption (Standard)	98W
Consumption (Standby)	≤1W
Power Supply	AC100~240V (+/-10%),50/60 Hz
Weight	35kg
Dimensions(no base)	1283.00 × 755.00 × 49.10mm
Work Environment	Temperature: 0℃~50℃
	Humidity: 20%-90%
Accessory	
Standard	VGA cable, power cable
Optional	Pedestal, hanging bracket

\*Design and specifications are subject to change without notice.

### Dimensions

