



Fiber Optic Component  
Wall Mount LUI



## FEATURES

- ▶ Suitable for interconnect in cables distribution or between cables and optical equipments.
- ▶ Can manage both splices and terminations.
- ▶ Rubber fiber slotted bracket built-in, metal splice shelf to protect the fibers.
- ▶ Snap-in locker design, easy to change adapter panels for flexible configuration & easy installation.
- ▶ Top & bottom cable entry is easy with rubber plug.
- ▶ Space saving with its compact & small design of enclosure.
- ▶ Front door design is easy for operation & fibers expansion.
- ▶ Can include adapter panels for maximum 24 ports LC/SC and 12 ports ST/FC terminations.

## APPLICATION

- ▶ Optical fiber access network.
- ▶ Local area networks.
- ▶ Fiber to the premises.
- ▶ Small-count splice applications.

## SPECIFICATION

Parts	Material	Dimension	Remarks
Metal Shelf	Alum., 1.0mm Thickness	320x250x55mm (LxWxH)	Black or Beige
Splice Tray	Alum., 0.6mm Thickness	142x116x11mm (LxWxH)	12 fibers/Tray, 2 trays Max.
Adapter Panel	Alum., 1.5mm Thickness	175x37mm (WxH)	1 Panel, Black or Beige
Cable Plug	Rubber	28mm Diameter	For 4 Cable Entries
Cable Saddle	Plastic	28x24mm Inner Ring	2 pcs, with foam sticker

### ORDERING INFORMATION:

NLU-FXXUXXW-06 : LIU 6 PORT Wall Mount - UnLoaded

NLU-FXXUXXW-12 : LIU 12 PORT Wall Mount - UnLoaded

NLU-FXXUXXW-24 : LIU 24 PORT Wall Mount - UnLoaded