





Floor Standing Steel Racks designed for Servers, Networking, Data Centers, Audio Video, Telecom and Lab applications. Racks are fabricated out of CRCA steel, CNC programmed, punched, bended, welded and Powder coated with highest quality standards.

Configuration for standard racks are welded frame with 4 pillars of multi Fold profile welded to top and bottom panels. 4 Fold profile depth rails to additionally support the rack. Removable side panels partially vented for better air circulation. Openings/Cut outs for field cable entry from Top & Bottom of the Rack. Vented top cover with fan mounting provision, Front Glass or perforated Metal door with lock and key. Back Vented or perforated metal door with lock and key. Free Floor standing Design with 4 No. castor wheels, 2 no's with breaks and 2 no's without breaks. Levelers or Plinth can be provided on request. Racks are available in 27U, 36U & 42U Variants with 650mm/800mm/1000mm deep configuration and 600 and 800 width configurations.

FEATURES

- Adjustable 19" equipment mounting verticals provide the better mounting flexibility maxmizing the usable mounting space.
- Top and bottom Panel with ventilation and cable entry facility.
- ► Powder coated finish with pretreatment process meeting all industry standards.
- Depth adjustable mounting slots.
- Precision engineering capabilities and best efficient software configuration product technology provides the best product quality and fastest delivery in the industry.
- Provision to mount the cooling fans on the top panel.
- Grounding and Bonding Options.
- ► 100% assured compatibility with all equipment conforming to DIN 41494. General industrial standard for equipment.

SPECIFICATION

Rack Standard: Conforms to DIN 41494 or equivalent standard

Front Door: Lockable Toughened Glass Door

Equipment Mounting: DIN Standard 10mm Sq. Slots / Direct M6 Tap

Standard Finish: Powder Coated

Standard Mounting Option: Castor wheels (Front 2 wheels with Break and rear without break)

Or Levelers

Construction: Welded or CKD (knockdown)

Basic Frame: Steel

Mounting Angle: 19" Mounting angles made of formed steel

Top and Bottom Cover: Welded to Frame, Vented and Cable entry/exit cut outs from Top & Bottom.

Static Load: 500KGs

Standard Color: Grey or Black







